

## Coils and Electronics

### C13

Standard Coil

www: [www.salushydraulics.pl](http://www.salushydraulics.pl)  
 e-mail: [pl@salushydraulics.pl](mailto:pl@salushydraulics.pl)  
 shop/sklep: [www.salushydraulics.pl/sklep/](http://www.salushydraulics.pl/sklep/)

#### ■ PERFORMANCE DATA

Duty cycle	100% at 110% rated voltage between -20°C and 40°C	400AA00031A, C13DM12/14
Magnet wire insulation	200°C [392° F]	
Input Voltage Range	90% to 110% of rated voltage	

#### ■ MODEL CODE

**C13 - H - 24 - 22**

**Coil Series**  
C13 -13 mm tube

**Connector Type**

Code	Connector Type
H	DIN43650 ISO Standard
F	Flying Leads [12 and 24 VDC only]
DM	Deutsch Moulded [12 and 24 VDC only]

**Coil Power**  
14 -14 Watt  
22 -22 Watt  
27 -27 Watt

**Coil Voltage**

Code	Coil Voltage
12	12 VDC
24	24 VDC
110	110 VAC*
220	220 VAC*

\*External rectifier required: AXP9997-115 or AXP9997-230

#### ■ DIMENSIONS

mm [in]

