

## Coils and Electronics

### C13

Standard Coil

www: [www.salushydraulics.pl](http://www.salushydraulics.pl)  
 e-mail: [pl@salushydraulics.pl](mailto:pl@salushydraulics.pl)  
 shop/sklep: [www.salushydraulics.pl/sklep/](http://www.salushydraulics.pl/sklep/)

#### ■ PERFORMANCE DATA

Duty cycle	100% at 110% rated voltage between -20°C and 40°C
Magnet wire insulation	200°C [392° F]
Input Voltage Range	90% to 110% of rated voltage

400AA00033A, C13DM24/14

#### ■ MODEL CODE

**C13 - H - 24 - 22**

<p><b>Coil Series</b> C13 -13 mm tube</p>	<p><b>Connector Type</b></p> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>Code</th> <th>Connector Type</th> </tr> </thead> <tbody> <tr> <td>H</td> <td>DIN43650 ISO Standard</td> </tr> <tr> <td>F</td> <td>Flying Leads [12 and 24 VDC only]</td> </tr> <tr> <td>DM</td> <td>Deutsch Moulded [12 and 24 VDC only]</td> </tr> </tbody> </table>	Code	Connector Type	H	DIN43650 ISO Standard	F	Flying Leads [12 and 24 VDC only]	DM	Deutsch Moulded [12 and 24 VDC only]	<p><b>Coil Power</b> 14 -14 Watt 22 -22 Watt 27 -27 Watt</p> <p><b>Coil Voltage</b></p> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>Code</th> <th>Coil Voltage</th> </tr> </thead> <tbody> <tr> <td>12</td> <td>12 VDC</td> </tr> <tr> <td>24</td> <td>24 VDC</td> </tr> <tr> <td>110</td> <td>110 VAC*</td> </tr> <tr> <td>220</td> <td>220 VAC*</td> </tr> </tbody> </table> <p><small>*External rectifier required: AXP9997-115 or AXP9997-230</small></p>	Code	Coil Voltage	12	12 VDC	24	24 VDC	110	110 VAC*	220	220 VAC*
Code	Connector Type																			
H	DIN43650 ISO Standard																			
F	Flying Leads [12 and 24 VDC only]																			
DM	Deutsch Moulded [12 and 24 VDC only]																			
Code	Coil Voltage																			
12	12 VDC																			
24	24 VDC																			
110	110 VAC*																			
220	220 VAC*																			

#### ■ DIMENSIONS

mm [in]

