



TECHNICAL DATA

MAX. OPERATING PRESSURE	350 bar
MAX. FLOW	60 l/min
SETTING RANGE	140 - 350 bar
SETTING	350 bar cracking pressure
PRESSURE INCREASE	170 bar/turn
PILOT RATIO	3:1
MAX. INTERNAL LEAKAGE AT 85% OF PRESSURE SETTING	5 drops/min. from 1 to 2
PRESSURE SETTING AT LEAST 1.3 TIMES THE MAX. LOAD INDUCED PRESSURE	
HYDRAULIC FLUID	Mineral based or synthetics oil
FLUID TEMPERATURE RANGE	-30 to 100°C
VISCOSITY RANGE	10 to 500 mm²/s (cSt)
FILTRATION	10 µm (NAS 8) ISO 4406 19/17/14
INSTALLATION TORQUE	40-45 Nm
WEIGHT	0.15 Kg
CAVITY	SUN T11A
VALVE MATERIAL	Steel, external surfaces zinc plated

REVISIONS
DESCRIPTIONS

DIMENSIONS mm		TITLE	
CAVITY N.	ANGLE PROJECTION	VENTILATA T11A 3:1 TV 350	
REQUEST N.		SPECIFICATIONS	
SEAL KIT		Setting range = 140-350 bar - Taratura/setting = 350 bar I.A.	
		CUSTOMER AND PART NUMBER	
		SCALE	WEIGHT
		2:1	0.145
		REVISIONS	
		DRAWING BY	DATE
		Moretti	30/05/16
		REPLACES DRW. N.	DRAWING N.
			PJ16017F0i

